



**SCATTERGOOD  
& JOHNSON LTD**



Certificate number 734/95

ELECTRICAL ENGINEERING AND FLUID CONTROL DISTRIBUTORS

- \* Flexible mains cable with a tinned steel wire armour braid and transparent PVC outer sheath. The type of construction offers flexibility and protection against mechanical damage.
- \* Used as measuring and control cables in tool machines, conveyor belts, production lines in factory automation.
- \* Grey outer sheath of special PVC compound, braiding of oxidation-protected steel wire, transparent external sheath.
- \* The galvanised steel wire braid provides partial screening.
- \* Black cores numbered in white underlined to avoid confusion.
- \* Flame retardant (IEC 332.1)
- \* Voltage rating 300/500V.
- \* Manufactured to VDE specifications.

\* No earth provided in 2 Core Cables.

**Oskar Lapp**

**ÖLFLEX® CLASSIC 110 SY**



Note : Each cable contains a green/yellow earth core. A 4 core cable consists of 3 numbered cores + a green/yellow earth core.

No. of cores	Conductor mm <sup>2</sup>	Lapp Cable Part No.	Outer cable diameter mm	Approx. Weight kg/100M	Part Number	Reel	Price
2*	0.75	1125802	8.2	9.7	SY2C/0.75/100/R	100M	£87.30
2*	1.0	1125852	8.5	10.6	SY2C/1.0/100/R	100M	£103.42
2*	1.5	1125902	9.3	12.8	SY2C/1.5/100/R	100M	£123.70
3	0.75	1125103	8.5	10.8	SY3C/0.75/100/R	100M	£107.90
3	1.0	1125203	8.8	11.9	SY3C/1.0/100/R	100M	£120.10
3	1.5	1125303	9.7	15.1	SY3C/1.5/100/R	100M	£149.10
3	2.5	1125403	11.1	20.6	SY3C/2.5/100/R	100M	£216.86
3	4.0	1125503	12.0	28.5	SY3C/4.0/50/R	50M	£155.53
4	0.5	1125004	8.5	10.7	SY4C/0.5/100/R	100M	£101.76
4	0.75	1125104	9.2	12.6	SY4C/0.75/100/R	100M	£126.72
4	1.0	1125204	9.5	14.1	SY4C/1.0/100/R	100M	£141.86
4	1.5	1125304	10.2	17.3	SY4C/1.5/100/R	100M	£178.92
4	2.5	1125404	12.1	24.9	SY4C/2.5/100/R	100M	£267.80
4	4.0	1125505	14.0	34.8	SY4C/4.0/50/R	50M	£197.36
4	6.0	1125604	16.2	48.2	SY4C/6.0/50/R	50M	£289.03
4	10.0	1125614	19.4	73.1	SY4C/10.0/50/R	50M	£458.11
4	16.0	1125624	22.4	138.4	SY4C/16.0/50/R	50M	£694.03
5	0.75	1125105	9.7	14.6	SY5C/0.75/100/R	100M	£142.72
5	1.0	1125205	10.1	16.4	SY5C/1.0/100/R	100M	£165.38
5	1.5	1125305	11.1	20.2	SY5C/1.5/100/R	100M	£205.94
5	2.5	1125405	13.2	29.5	SY5C/2.5/100/R	100M	£304.00
5	4.0	1125505	15.1	41	SY5C/4.0/50/R	50M	£244.85
5	6.0	1125605	17.7	57.9	SY5C/6.0/50/R	50M	£339.77
7	0.75	1125107	10.3	17.2	SY7C/0.75/100/R	100M	£174.30
7	1.0	1125207	11.0	20	SY7C/1.0/100/R	100M	£208.42
7	1.5	1125307	11.9	24.8	SY7C/1.5/50/R	50M	£138.12
7	2.5	1125407	14.3	37.3	SY7C/2.5/50/R	50M	£197.16
12	0.5	1125012	11.9	21.3	SY12C/0.5/100/R	100M	£206.88
12	0.75	1125112	12.9	26	SY12C/0.75/100/R	100M	£274.78
12	1.0	1125212	13.9	30.9	SY12C/1.0/100/R	100M	£341.20
12	1.5	1125312	15.4	39.6	SY12C/1.5/50/R	50M	£223.92
18	0.75	1125118	14.9	35.5	SY18C/0.75/50/R	50M	£189.59
18	1.0	1125218	15.9	41.5	SY18C/1.0/50/R	50M	£230.22
18	1.5	1125318	17.6	53.8	SY18C/1.5/50/R	50M	£303.74
18	2.5	1125418	21.4	82.3	SY18C/2.5/50/R	50M	£529.18
25	0.75	1125125	17.0	46.5	SY25C/0.75/50/R	50M	£239.49
25	1.0	1125225	18.1	54.8	SY25C/1.0/50/R	50M	£326.42
25	1.5	1125325	20.3	71.3	SY25C/1.5/50/R	50M	£408.35

Leeds  
Tel: 0113 243 0203

Sheffield  
Tel: 0114 243 1841

Gateshead  
Tel: 0191 460 2233

Manchester  
Tel: 0161 876 4337

Glasgow  
Tel: 0141 892 0166

Walsall  
Tel: 01922 403426

email: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)