



- * 22.5mm single mounting hole
- * All actuators are supplied complete with contact block carrier
- * Maximum Voltage 600 V AC, 250 V DC
- * Current rating 1.2A @ 600 V AC
- * Current rating 0.3A @ 250 V DC
- * Certified to CSA and Lloyds
- * Comply with BS, IEC, VDE & UL
- * Degree of protection IP65



Non-Illuminated

Flush Push Button Operators



Part Number	Actuator Style	Colour	Action
44/701/200	Flush	●	Momentary
44/701/202		●	
44/701/204		●	
44/701/205		●	
44/701/206		●	
44/701/209		○	
44/702/200	Flush	●	Maintained
44/702/202		●	
44/702/204		●	
44/702/205		●	
44/702/206		●	
44/702/209		○	

N.B Add Contact Blocks Only

Extended Push Button Operators



Part Number	Actuator Style	Colour	Action
44/704/200	Extended	●	Momentary
44/704/202		●	
44/704/204		●	
44/704/205		●	
44/704/206		●	
44/704/209		○	

N.B Add Contact Blocks Only

Palm Push Button Operators



Part Number	Actuator Style	Colour	Action
44/707/200	Palm Push	●	Momentary
44/707/202		●	
44/707/205		●	

N.B Add Contact Blocks Only

Emergency Stop Push Button Operators



Part Number	Actuator Style	Colour	Action
44/711/00	37mm Palm Push, Foolproof EN418	●	Twist Release
44/712/00			
44/710/00			Key Release
44/713/00			

N.B Add Contact Blocks Only

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk