



- * Unique clip-action terminal shrouds
- * Fully shrouded for personal safety
- * Voltage ratings of up to 550 V AC
- * 80kA breaking capacity AC
- * Maximum operating ambient temperature of +40oC
- * DIN Rail mounting feature on 32, 63 and 125 Amp
- * ASTA type test certified to BS 88: parts 1 and 6, CSA approved
- * Conforms to IEC 269-1

GE

Safeclick Fuse Holders



20Amp Fuse Holders

Part Number	Colour	Description	Voltage	Fuse Link Size
SC20H/BLK	●	Front connected	240 V AC	E1 (SS)
SC20H/WHI	○			
SC20H/GRN	●			
SC20P/BLK	●	Back stud connected		
SC20P/WHI	○			
SC20P/GRN	●			
SC20BH/BLK	●	Busbar/Front connected		

32Amp Fuse Holders

Part Number	Colour	Description	Voltage	Fuse Link Size
SC32HD/BLK	●	Front connected	550 V AC	F1 (NS)
SC32HD/WHI	○			
SC32HD/GRN	●			
SC32P/BLK	●	Back stud connected		
SC32P/WHI	○			
SC32P/GRN	●			
SC32PHD/BLK	●	Front/Back stud connected		
SC32PHD/WHI	○			
SC32BH/BLK	●	Busbar / Front connected		

63Amp Fuse Holders

Part Number	Colour	Description	Voltage	Fuse Link Size
SC63HD/BLK	●	Front connected	550 V AC	F2 (ES)
SC63HD/WHI	○			
SC63P/BLK	●	Back stud connected		
SC63BH/BLK	●	Busbar/Front connected		

100Amp Fuse Holders

Part Number	Colour	Description	Voltage	Fuse Link Size
SC100H/BLK	●	Front connected	415 V AC	(OS)

125Amp Fuse Holders

Part Number	Colour	Description	Voltage	Fuse Link Size
SC125HD/BLK	●	Front connected	440 V AC	(XS)

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk