



- * PBT housing with nickel coated copper locking nut
- * 4A nominal current
- * 30V AC / DC nominal voltage
- * Ingress Protection IP67 in locked position
- * Operating temperature -25°C to +90°C
- * 2 x LED status indicators
- * Maximum conductor size 0.75mm²
- * CE, UL Approvals

Lumberg

M12 Wireable LED Screw Connectors



LED Female (Packs of 5)

M12 Wireable LED Screw Connectors (Packs of 5) - Female

Style	Part Number	No. Wired Pins	Format	Style	Cable Gland Diameter (mm)
	RKC/LED4/7/PK	4	4 Pole	Straight	0.3 - 6.5
	RKCW/LED4/7/PK	4	4 Pole	Elbow	0.3 - 6.5

Lumberg



M12 Wireable Hex Nut Connectors



- * PBT housing with stainless steel hex locking nut
- * 4A nominal current at 40°C
- * 30V AC / DC nominal voltage
- * Ingress Protection IP69K in locked position
- * Operating temperature -25°C to +90°C
- * Hex nut connection for achieving IP69K protection
- * Maximum conductor size 0.75mm²
- * CE, UR Approvals

Female (Packs of 5)

M12 Wireable Hex Nut Connectors (Packs of 5) - Female

Style	Part Number	No. Wired Pins	Format	Style	Cable Gland Diameter (mm)
	RKCN4/7/PK	4	4 Pole	Straight	0.3 - 6.5
	RKCN5/7/PK	5	5 Pole		0.3 - 6.5
	RKCWN4/7/PK	4	4 Pole	Elbow	0.3 - 6.5
	RKCWN5/7/PK	5	5 Pole		0.3 - 6.5

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk