



# Hawke

## Non-Armoured Cable Glands



### Certification Information

- \* Certification Number BAS06ATEX0056X
- \* Approved to II 2GD Exd Exe IIC
- \* Ingress Protection IP66, IP67 and IP68 (30m for 7 days)
- \* Ambient Temperature Range -60°C to +100°C

### Features

- \* Manufactured from brass
- \* Provides seal on inner sheath
- \* For use with non-armoured elastomer and plastic cables
- \* Nickel plated cable glands are also available
- \* NPT threaded cable glands are also available

Zone 0



Zone 1



Zone 2



Zone 20



Zone 21



Zone 22



IEC Ex



### Non-Armoured Cable Glands

| Part Number | Gland Size | Thread Size | Cable Acceptance Details (mm) |      |              |      |
|-------------|------------|-------------|-------------------------------|------|--------------|------|
|             |            |             | Inner Sheath                  |      | Outer Sheath |      |
|             |            |             | Min.                          | Max. | Min.         | Max. |
| 501/421/0S  | 0S         | M20         | -                             | -    | 3.0          | 8.0  |
| 501/421/0   | 0          | M20         | -                             | -    | 7.5          | 11.9 |
| 501/421/A   | A          | M20         | -                             | -    | 11.0         | 14.3 |
| 501/421/B   | B          | M25         | -                             | -    | 13.0         | 20.2 |
| 501/421/C   | C          | M32         | -                             | -    | 19.0         | 26.5 |
| 501/421/C2  | C2         | M40         | -                             | -    | 25.0         | 32.5 |
| 501/421/D   | D          | M50         | -                             | -    | 31.5         | 44.4 |

# Hawke

## Non-Armoured Cable Gland Kits



### Certification Information

- \* Certification Number BAS06ATEX0056X
- \* Approved to II 2GD Exd Exe IIC
- \* Ingress Protection IP66, IP67 and IP68 (30m for 7 days)
- \* Ambient Temperature Range -60°C to +100°C

### Features

- \* Manufactured from brass
- \* Provides seal on inner sheath
- \* For use with non-armoured elastomer and plastic cables
- \* Supplied with locknut, serrated washer and nylon sealing washer

Zone 0



Zone 1



Zone 2



Zone 20



Zone 21



Zone 22



IEC Ex



### Non-Armoured Cable Gland Kits

| Part Number | Gland Size | Thread Size | Cable Acceptance Details (mm) |      |              |      |
|-------------|------------|-------------|-------------------------------|------|--------------|------|
|             |            |             | Inner Sheath                  |      | Outer Sheath |      |
|             |            |             | Min.                          | Max. | Min.         | Max. |
| K501/421/0S | 0S         | M20         | -                             | -    | 3.0          | 8.0  |
| K501/421/0  | 0          | M20         | -                             | -    | 7.5          | 11.9 |
| K501/421/A  | A          | M20         | -                             | -    | 11.0         | 14.3 |
| K501/421/B  | B          | M25         | -                             | -    | 13.0         | 20.2 |

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)