



Certification Information

- * Certification Number TUV99ATEX1407
- * Approved to II 2G EEx ia IIB T5
- * Ingress Protection IP68
- * Ambient Temperature Range -20°C to +70°C

Features

- * Polypropylene float
- * Contact closes as float rises
- * Supplied with 5m 2 core 0.75mm² PVC cable
- * Suitable galvanic isolators include KFD2-SR2-EX1.W or equivalent

Pepperl & Fuchs

NAMUR Liquid Level Float Switches



Zone 0

X

Zone 1

✓

Zone 2

✓

Zone 20

X

Zone 21

X

Zone 22

X

IEC Ex

X

NAMUR Liquid Level Float Switches

Part Number	Description	Switch Angle	Output	Dimensions (mm)	
				Diameter	Length
LFL1-CK-N-PVC5	Cylindrical Float Switch	±12°	NAMUR	29.2	135
LFL1-BK-N-PVC5	Ball Float Switch			86	-

Certification Information

- * Certification Number KEMA01ATEX1089
- * Approved to II 1/2GD EEx ia IIC T3-T6
- * Ingress Protection IP66 and IP67
- * Ambient Temperature Range -50°C to +70°C

Features

- * Polyester housing with stainless steel wetted parts
- * 1" BSP process connection
- * Suitable for liquids with a viscosity up to 10000 mm²/s
- * Suitable for process temperatures of -50°C to +150°C up to 64 bar
- * Optional overspill protection
- * M20 entry
- * Suitable galvanic isolators include KFD2-SR2-EX1.W or equivalent

Pepperl & Fuchs

NAMUR Vibration Level Switches



Zone 0

✓

Zone 1

✓

Zone 2

✓

Zone 20

X

Zone 21

✓

Zone 22

✓

IEC Ex

X

NAMUR Vibration Level Switches

Part Number	Description	Switch Function	Output	Dimensions (mm)	
				Housing Diameter	Process Connection Length
LVL-M1G31AAP1N1NAE2	Without Overspill Protection	Low to High	NAMUR	85	69
LVL-M1G31AAP1N1NAEB	With Overspill Protection				

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk