



Certification Information

- * Certificate Number LCIE01ATEX6073
- * Approved to II 2GD EExd IIC T4 (100W) or T5 (50W)
- * Ingress Protection IP65
- * Ambient Temperature Range -20°C to +40°C

Features

- * Black anodised aluminium enclosure
- * High performance cartridge heating element
- * DIN rail mounted (vertical) either on short or long side
- * Supplied with 1m 3 core 0.75mm² cable

Stego Panel Heaters



Zone 0

X

Zone 1

✓

Zone 2

✓

Zone 20

X

Zone 21

✓

Zone 22

✓

IEC Ex

X

Panel Heaters

Part Number	Voltage	Rating (W)	Dimensions (mm)			Weight (kg)
			Height	Width	Depth	
CREX/02010.0-00	230 - 240V AC	50	150	69	118	1.3
CREX/02011.0-00		100	180			1.5
CREX/02010.0-01	110 - 120V AC	50	150			1.3
CREX/02011.0-01		100	180			1.5

Stego Thermostats



Certification Information

- * Certificate Number LCIE01ATEX6074
- * Approved to II 2GD EExd IIC T6
- * Ingress Protection IP65
- * Ambient Temperature Range -20°C to +40°C

Features

- * Black anodised aluminium enclosure
- * Contact opens with rising temperature
- * Thermostatic bimetal element
- * Small switch temperature difference of 4k (±1k)
- * Supplied with 1m 3 core 0.75mm² cable

Zone 0

X

Zone 1

✓

Zone 2

✓

Zone 20

X

Zone 21

✓

Zone 22

✓

IEC Ex

X

Panel Thermostats

Part Number	Description	Switch Rating	Switch-Off Temperature (°C)	Mounting	Weight (kg)
REX/01180.0-00	Thermostat	4A SPST	15	M8 via Bracket (Supplied)	0.2
REX/01181.0-00			25		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk