



- * 22.5mm single mounting hole
- * All actuators are supplied complete with contact block carrier
- * Maximum Voltage 600 V AC, 250 V DC
- * Current rating 1.2A @ 600 V AC
- * Current rating 0.3A @ 250 V DC
- * Certified to CSA and Lloyds
- * Comply with BS, IEC, VDE & UL
- * Degree of protection IP65



Non-Illuminated

Selector Switches, 2 Position



Part Number	Actuator Style	Colour	Action
44/720/200	Lever	●	Maintained
44/722/200			Spring Return

N.B Add Contact Blocks Only

Selector Switches, 3 Position



Part Number	Actuator Style	Colour	Action
44/724/200	Lever	●	Maintained
44/726/200			Spring Return From Right
44/727/200			Spring Return From Left
44/725/200			Spring Return From Left and Right

N.B Add Contact Blocks Only

Key Operated Selector Switches, 2 Position



Part Number	Key Removable	Colour	Action
44/730/201	Left	●	Maintained
44/730/202	Left and Right		
44/732/201	Left		Spring Return

N.B Add Contact Blocks Only

Key Operated Selector Switches, 3 Position



Part Number	Key Removable	Colour	Action
44/734/201	Centre	●	Maintained
44/734/203	Left and Centre		
44/734/204	Right and Centre		
44/734/205	All		Spring Return From Left
44/737/201	All		
44/737/204	Left and Centre		
44/736/201	Centre		
44/736/203	Right and Centre		Spring Return From Right

N.B Add Contact Blocks Only

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk