



- * SAFECLIP SS, NS, ES, XS - Offset blade tag
- * SAFECLIP OS - Offset tags: 2-hole fixing
- * Voltage rating up to 440 V AC
- * 80kA breaking capacity AC
- * Maximum operating ambient temperature of +40°C
- * ASTA 20 certified (to 80kA, 440V), BS 88-1 or 6:1988, IEC 269-1



SS Fuses To Fit SC20 Fuse Holders

Part Number	Fuse Rating		Class	Fuse Holder	Fixing Centres	Pack Qty
SS2	2A	240 V AC	E1 General Purpose	SC20	Blade Type	20
SS4	4A					
SS6	6A					
SS10	10A					
SS16	16A					
SS20	20A					

NS Fuses To Fit SC32 Fuse Holders

Part Number	Fuse Rating		Class	Fuse Holder	Fixing Centres	Pack Qty
NS2	2A	440 V AC	F1 General Purpose	SC32	Blade Type	20
NS4	4A					
NS6	6A					
NS10	10A					
NS16	16A					
NS20	20A					
NS25	25A					
NS32	32A	415 V AC	F1 Motor Rated to 40A			
NS32M40	32A					

ES Fuses To Fit SC63 Fuse Holders

Part Number	Fuse Rating		Class	Fuse Holder	Fixing Centres	Pack Qty
ES40	40A	440 V AC	F2 General Purpose	SC63	Blade Type	20
ES50	50A					
ES63	63A					
ES63M80	63A	415 V AC	F2 Motor Rated to 80A			

OS Fuses To Fit SC100 Fuse Holders

Part Number	Fuse Rating		Class	Fuse Holder	Fixing Centres (mm)	Pack Qty
OS80	80A	440 V AC	General Purpose	SC100	73.0	20
OS100	100A					
OS100M125	100A	415 V AC	Motor Rated to 125A			
OS100M160			Motor Rated to 160A			

XS Fuses To Fit SC125 Fuse Holders

Part Number	Fuse Rating		Class	Fuse Holder	Fixing Centres	Pack Qty
XS2	2A	440 V AC	General Purpose	SC125	Blade Type	10
XS4	4A					
XS6	6A					
XS10	10A					
XS16	16A					
XS20	20A					
XS25	25A					
XS32	32A					
XS35	35A					
XS40	40A					
XS50	50A					
XS63	63A					
XS80	80A					
XS100	100A					
XS125	125A					

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk