



- * Available in insulated and steel enclosures
- * All switches lockable in the OFF position (using up to three padlocks)
- * All enclosures with metric knockouts
- * Totally insulated enclosures offer enhanced safety
- * Self-extinguishing polycarbonate, halogen-free
- * Dust, moisture, impact and chemical resistant
- * Operating temperature from -25°C up to +40°C
- * UL, CSA
- * All switches to IEC/EN60-204 & IEC/EN60-947 Pt4
- * Degree of protection IP65

Moeller

Enclosed Isolators



3 Pole Isolators - Insulated Enclosures IP65

| Part Number | Rated Uninterrupted Current Iu (A) | kW rating AC23 @ 415V | kW rating AC3 @ 415V | Main Poles |
|----------------|------------------------------------|-----------------------|----------------------|------------|
| T0-2-1/I1H/SVB | 20 | 6.5 | 4 | 3 |
| P1-25/I2H/SVB | 25 | 13 | 7.5 | |
| P1-32/I2H/SVB | 32 | 15 | 13 | |
| P3-63/I4/SVB | 63 | 37 | 30 | |
| P3-100/I5/SVB | 100 | 50 | 37 | |

3 Pole Isolators - Metal Enclosures IP55

| Part Number | Rated Uninterrupted Current Iu (A) | kW rating AC23 @ 415V | kW rating AC3 @ 415V | Main Poles |
|---------------|------------------------------------|-----------------------|----------------------|------------|
| T0-2-1/ST/SVB | 20 | 6.5 | 4 | 3 |
| P1-25/ST/SVB | 25 | 13 | 7.5 | |
| P1-32/ST/SVB | 32 | 15 | 13 | |
| P3-63/ST/SVB | 63 | 37 | 30 | |
| P3-100/ST/SVB | 100 | 50 | 37 | |

6 Pole Isolators - Insulated Enclosures IP65

| Part Number | Rated Uninterrupted Current Iu (A) | kW rating AC23 @ 415V | kW rating AC3 @ 415V | Main Poles |
|-----------------|------------------------------------|-----------------------|----------------------|------------|
| T0-3-8342/I1SVB | 20 | 6.5 | 4 | 6 |
| T3-3-8342/I2SVB | 32 | 13 | 12 | |
| T5B-3-8342I4SVB | 63 | 22 | 22 | |
| T5-3-8342/I5SVB | 100 | 30 | 30 | |

Accessories

| Part Number | Description | For use with |
|-------------|------------------------|--|
| N-P1Z | Switched Neutral Poles | Rear Mounting and enclosed P1 isolators |
| N-P3Z | | Rear Mounting and enclosed P3 isolators |
| HI11-P1/P3Z | Auxiliary contacts | 1 N/O + 1 N/C for rear mounting and enclosed P1/P3 isolators |

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk