



- * All switches to IEC/EN60-204 & IEC/EN60-947 Pt3
- * Padlockable in the OFF position (using up to three padlocks)
- * Operating temperature -25°C to +50°C
- * DIN Rail / screw fix or front door mounting
- * Worldwide approvals
- * Degree of protection IP65 (handle)

Moeller

Panel Mounted Isolators



Rear Mounting Door Interlocked Isolators




Part Number	Rated Uninterrupted Current I _v (A)	KW rating AC23 @ 415V	KW rating AC3 @ 415V	Main Poles
T0-2-1/V/SVB	20	6.5	4	3
P1-25/V/SVB	25	13	7.5	
P1-32/V/SVB	32	15	13	
P3-63/V/SVB	63	37	30	
P3-100/V/SVB	100	50	37	

Front Door Mounting Isolators



Part Number	Rated Uninterrupted Current I _v (A)	KW rating AC23 @ 415V	KW rating AC3 @ 415V	Main Poles
T0-2-1/EA/SVB	20	6.5	4	3
P1-25/EA/SVB	25	13	7.5	
P1-32/EA/SVB	32	15	13	
P3-63/EA/SVB	63	37	30	
P3-100/EA/SVB	100	50	37	

Accessories for Rear Mounting and Front Door Mounting Isolators

Part Number	Description	For use with
N-P1E	 Switched neutral poles	Door mounting P1 isolators
N-P1Z		Rear Mounting and enclosed P1 isolators
N-P3E		Door mounting P3 isolators
N-P3Z		Rear Mounting and enclosed P3 isolators
HI11-P1/P3E	Auxiliary contacts	1 N/O + 1 N/C for door mounting P1/P3 isolators
HI11-P1/P3Z		1 N/O + 1 N/C for rear mounting and enclosed P1/P3 isolators
ZAV-T0	Plug-in shaft extensions	T0, T3 and P1 switches
ZAV-P3		T5(B) and P3 switches
ZVV-T0	Plug-in interlock extensions	T0, T3 and P1 switches
ZVV-P3		T5(B) and P3 switches

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk