



- \* PKZ series combines isolation, short circuit protection, thermal protection & motor switching in a single unit
- \* Switching capacity 100/50/16kA/415V
- \* One range of clip-on accessories
- \* Rotary handle gives immediate on/off indication
- \* Open operating temperature -25°C to +55°C
- \* Enclosed operating temperature -25°C to +40°C
- \* DIN Rail mounting
- \* Worldwide approvals
- \* Degree of protection IP20



### PKZM0 Basic Units. (Rotary Handle 0.1 - 32Amp)

Part Number	kW rating AC3 @ 415V	Rated Operational, Current, I <sub>v</sub> (A)	Overload Release Setting (A)	Short-circuit Release (A)
PKZM0-0.16	-	0.16	0.10 - 0.16	2.2
PKZM0-0.25	0.06	0.25	0.16 - 0.25	3.5
PKZM0-0.4	0.09	0.4	0.25 - 0.40	5.6
PKZM0-0.63	0.12	0.63	0.40 - 0.63	8.8
PKZM0-1	0.25	1	0.63 - 1.00	14
PKZM0-1.6	0.55	1.6	1.0 - 1.6	22
PKZM0-2.5	0.75	2.5	1.6 - 2.5	35
PKZM0-4	1.5	4	2.5 - 4.0	56
PKZM0-6.3	2.2	6.3	4.0 - 6.3	88
PKZM0-10	4	10	6.3 - 10	140
PKZM0-12	5.5	12	8.0 - 12	168
PKZM0-16	7.5	16	10 - 16	224
PKZM0-20	9	20	16 - 20	280
PKZM0-25	12.5	25	20 - 25	350
PKZM0-32	15	32	25 - 32	448

### PKZM01 Basic Units. (Push Button 0.1 - 16Amp)

Part Number	kW rating AC3 @ 415V	Rated Operational, Current, I <sub>v</sub> (A)	Overload Release Setting (A)	Short-circuit Release (A)
PKZM01-0.16	-	0.16	0.10 - 0.16	2.2
PKZM01-0.25	0.06	0.25	0.16 - 0.25	3.5
PKZM01-0.4	0.09	0.4	0.25 - 0.40	5.6
PKZM01-0.63	0.12	0.63	0.40 - 0.63	8.8
PKZM01-1	0.25	1	0.63 - 1.00	14
PKZM01-1.6	0.55	1.6	1.0 - 1.6	22
PKZM01-2.5	0.75	2.5	1.6 - 2.5	35
PKZM01-4	1.5	4	2.5 - 4.0	56
PKZM01-6.3	2.2	6.3	4.0 - 6.3	88
PKZM01-10	4	10	6.3 - 10	140
PKZM01-12	5.5	12	8.0 - 12	168
PKZM01-16	7.5	16	10 - 16	224

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)