



- * PKZ series combines isolation, short circuit protection, thermal protection & motor switching in a single unit
- * Switching capacity 100/50/16kA/415V
- * One range of clip-on accessories
- * Rotary handle gives immediate on/off indication
- * Open operating temperature -25°C to +55°C
- * Enclosed operating temperature -25°C to +40°C
- * DIN Rail mounting
- * Worldwide approvals
- * Degree of protection IP20



PKZM4 Basic Units. (Rotary Handle 10 - 63Amp)

Part Number	kW rating AC3 @ 415V	Rated Operational Current, I _v (A)	Overload Release Setting (A)	Short-circuit Release (A)
PKZM4-16	7.5	16	10 - 16	224
PKZM4-25	12.5	25	16 - 25	350
PKZM4-32	15	32	25 - 32	448
PKZM4-40	20	40	32 - 40	560
PKZM4-50	25	50	40 - 50	700
PKZM4-58	30	58	50 - 58	812
PKZM4-63	34	63	55 - 63	882

Accessories

Accessories for use with PKZM0, PKZM01, PKZM4

Part Number	Description	Voltage/Colour/Size
NHI11-PKZ0	Side-mounting auxiliary contacts	1 N/O + 1N/C
NHI12-PKZ0		1 N/O + 2N/C
NHI21-PKZ0		2 N/O + 1 N/C
NHI-E-11-PKZ0	Front-mounting auxiliary contacts	1 N/O + 1N/C
NHI-E-10-PKZ0		1 N/O
AGM2-10-PKZ0	Trip-indicating auxiliary contacts	1 N/O
AGM2-01-PKZ0		1 N/C
A-PKZ0/024VAC	Shunt releases	24V 50Hz
A-PKZ0/110VAC		110V 50Hz
A-PKZ0/240VAC		240V 50Hz
A-PKZ0/415VAC		415V 50Hz
U-PKZ0/024VAC	Undervoltage releases	24V 50Hz
U-PKZ0/110VAC		110V 50Hz
U-PKZ0/240VAC		240V 50Hz
U-PKZ0/415VAC		415V 50Hz
H-PKZ0	Door coupling rotary handles	●
PKZ0-XRH		●
AK-PKZ0	Lockable handles	●
B3.0/2-PKZ0	Commoning Busbars PKZ0	2W Link 45mm Space
B3.0/4-PKZ0		4W Link 45mm Space
B3.1/2-PKZ0		2W Link 54mm Space
B3.1/3-PKZ0		3W Link 54mm Space
B3.1/4-PKZ0		4W Link 54mm Space
B3.1/5-PKZ0		5W Link 54mm Space
B3.2/4-PKZ0		4W Link 63mm Space
BK25/3-PKZ0		Connection Link

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk