



- * Identical Size AC+DC contactors
- * Low power consumption coils
- * Front coil connections
- * Twin box terminals
- * Integral suppression on DC contactors
- * Temperature rating from -25°C up to +60°C
- * DIN Rail / screw mounting
- * Worldwide approvals
- * IEC/EN 60947
- * Degree of protection IP20



xstart 3 Pole Contactors Frame Size A

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM7-10/024AC	24	-	3	1 N/O
DILM7-10/110AC	110	-		
DILM7-10/230AC	230	-		
DILM7-10/415AC	400	-		
DILM7-10/024DC	-	24		
DILM7-01/024AC	24	-		1 N/C
DILM7-01/110AC	110	-		
DILM7-01/230AC	230	-		
DILM7-01/415AC	400	-		
DILM7-01/024DC	-	24		

xstart 3 Pole Contactors Frame Size A

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM9-10/024AC	24	-	4	1 N/O
DILM9-10/110AC	110	-		
DILM9-10/230AC	230	-		
DILM9-10/415AC	400	-		
DILM9-10/024DC	-	24		
DILM9-01/024AC	24	-		1 N/C
DILM9-01/110AC	110	-		
DILM9-01/230AC	230	-		
DILM9-01/415AC	400	-		
DILM9-01/024DC	-	24		

xstart 3 Pole Contactors Frame Size A

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM12-10/024AC	24	-	5.5	1 N/O
DILM12-10/110AC	110	-		
DILM12-10/230AC	230	-		
DILM12-10/415AC	400	-		
DILM12-10/024DC	-	24		
DILM12-01/024AC	24	-		1 N/C
DILM12-01/110AC	110	-		
DILM12-01/230AC	230	-		
DILM12-01/415AC	400	-		
DILM12-01/024DC	-	24		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk