



- * Identical Size AC+DC contactors
- * Low power consumption coils
- * Front coil connections
- * Twin box terminals
- * Integral suppression on DC contactors
- * Temperature rating from -25°C up to +60°C
- * DIN Rail / screw mounting
- * Worldwide approvals
- * IEC/EN 60947
- * Degree of protection IP00



xstart 3 Pole Contactors Frame Size B

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM17-10/024AC	24	-	7.5	1 N/O
DILM17-10/110AC	110	-		
DILM17-10/230AC	230	-		
DILM17-10/415AC	400	-		
DILM17-10/024DC	-	24		
DILM17-01/024AC	24	-		1 N/C
DILM17-01/110AC	110	-		
DILM17-01/230AC	230	-		
DILM17-01/415AC	400	-		
DILM17-01/024DC	-	24		

xstart 3 Pole Contactors Frame Size B

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM25-10/024AC	24	-	11	1 N/O
DILM25-10/110AC	110	-		
DILM25-10/230AC	230	-		
DILM25-10/415AC	400	-		
DILM25-10/024DC	-	24		
DILM25-01/024AC	24	-		1 N/C
DILM25-01/110AC	110	-		
DILM25-01/230AC	230	-		
DILM25-01/415AC	400	-		
DILM25-01/024DC	-	24		

xstart 3 Pole Contactors Frame Size B

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM32-10/024AC	24	-	15	1 N/O
DILM32-10/110AC	110	-		
DILM32-10/230AC	230	-		
DILM32-10/415AC	400	-		
DILM32-10/024DC	-	24		
DILM32-01/24AC	24	-		1 N/C
DILM32-01/110AC	110	-		
DILM32-01/230AC	230	-		
DILM32-01/415AC	400	-		
DILM32-01/024DC	-	24		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk