



- * Identical Size AC+DC contactors
- * Low power consumption coils
- * Front coil connections
- * Twin box terminals
- * Integral suppression on DC contactors
- * Temperature rating from -25°C up to +60°C
- * DIN Rail / screw mounting
- * Worldwide approvals
- * IEC/EN 60947
- * Degree of protection IP00

Moeller

xStart 3 Pole Contactors (18.5-30kW)



xstart 3 Pole Contactors Frame Size C				
Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM40/024AC	24	-	18.5	None
DILM40/110AC	110	-		
DILM40/230AC	230	-		
DILM40/415AC	400	-		
DILM40/024DC	-	24		

xstart 3 Pole Contactors Frame Size C				
Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM50/024AC	24	-	22	None
DILM50/110AC	110	-		
DILM50/230AC	230	-		
DILM50/415AC	400	-		
DILM50/024DC	-	24		

xstart 3 Pole Contactors Frame Size C				
Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM65/024AC	24	-	30	None
DILM65/110AC	110	-		
DILM65/230AC	230	-		
DILM65/415AC	400	-		
DILM65/024DC	-	24		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk