



- * Identical Size AC+DC contactors
- * Low power consumption coils
- * Front coil connections
- * Twin box terminals
- * Integral suppression on DC contactors
- * Temperature rating from -25°C up to +60°C
- * DIN Rail / screw mounting
- * Worldwide approvals
- * IEC/EN 60947
- * Degree of protection IP00

Moeller

xStart 3 Pole Contactors (37-75kW)



xstart 3 Pole Contactors Frame Size D

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM80/024AC	24	-	37	None
DILM80/110AC	110	-		
DILM80/230AC	230	-		
DILM80/415AC	400	-		
DILM80/024DC	-	24		

xstart 3 Pole Contactors Frame Size D

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM95/024AC	24	-	45	None
DILM95/110AC	110	-		
DILM95/230AC	230	-		
DILM95/415AC	400	-		
DILM95/024DC	-	24		

xstart 3 Pole Contactors Frame Size D

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM115/RAC24	24	-	55	None
DILM115/RAC120	110	-		
DILM115/RAC240	230	-		
DILM115/RAC440	400	-		
DILM115/RDC24	-	24		

xstart 3 Pole Contactors Frame Size D

Part Number	Coil Voltage		kW Rating AC3 @ 400V	Auxiliary Contacts
	V AC	V DC		
DILM150/RAC24	24	-	75	None
DILM150/RAC120	110	-		
DILM150/RAC240	230	-		
DILM150/RAC440	400	-		
DILM150/RDC24	-	24		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk