



- * Identical Size AC+DC relays
- * Low power consumption coils
- * Front coil connections
- * Twin box terminals
- * Integral suppression on DC contactors
- * Temperature rating from -25°C up to +60°C
- * DIN Rail / screw mounting
- * Worldwide approvals
- * IEC/EN 60947
- * Degree of protection IP20

Moeller

xStart

4 Pole Relays & Auxiliary Blocks

4 Pole Relays



DILA 4 Pole Relays

Part Number	Coil Voltage		Contact Arrangement
	V AC	V DC	
DILA-22/024AC	24	-	2 N/O + 2 N/C
DILA-22/110AC	110	-	
DILA-22/230AC	230	-	
DILA-22/024DC		24	3 N/O + 1 N/C
DILA-31/024AC	24	-	
DILA-31/110AC	110	-	
DILA-31/230AC	230	-	
DILA-31/024DC		24	4 N/O
DILA-40/024AC	24	-	
DILA-40/110AC	110	-	
DILA-40/230AC	230	-	
DILA-40/024DC		24	

Auxiliary Blocks



DILA Auxiliary Blocks

Part Number	For Use with	Contact Arrangement	
DILA-XHI20	DILA RELAYS DILM7 - DILM32 CONTACTORS	2 N/O	
DILA-XHI11		1 N/O + 1 N/C	
DILA-XHI02		2 N/C	
DILA-XHI40		4 N/O	
DILA-XHI31		3 N/O + 1 N/C	
DILA-XHI22	DILA RELAYS DILM7 - DILM32 CONTACTORS	2 N/O + 2 N/C	
DILA-XHI13		1 N/O + 3 N/C	
DILA-XHI04		4 N/C	
DILA-XHIV22			2 N/O (1 EM) + 2 N/C (1 LB)

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk