



- * Standard 22.5mm fixing hole
- * Snap fitting modular design saves both assembly and fitting time
- * Temperature rating from -25°C up to +70°C
- * Worldwide approvals
- * Meets all relevant international standards.
- * Degree of protection IP66



Non-Illuminated

Flush Push Button Operators



Part Number	Actuator Style	Colour	Action
M22-D-X	Flush	Without	Momentary
M22-D-S		Black	
M22-D-W		White	
M22-D-R		Red	
M22-D-G		Green	
M22-D-Y		Yellow	
M22-D-B		Blue	
M22-D-R-X0		Red with center dot	
M22-D-G-X1		Green with center dot	
M22-D-S-X0		Black with center dot	

Extended Push Button Operators



Part Number	Actuator Style	Colour	Action
M22-DH-S	Extended	Black	Momentary
M22-DH-W		White	
M22-DH-R		Red	
M22-DH-G		Green	
M22-DH-Y		Yellow	
M22-DH-B		Blue	

Illuminated

Flush Illuminated Push Button Operators



Part Number	Actuator Style	Colour	Action
M22-DL-W	Flush	White	Momentary
M22-DL-R		Red	
M22-DL-G		Green	
M22-DL-Y		Yellow	
M22-DL-B		Blue	

Extended Illuminated Push Button Operators



Part Number	Actuator Style	Colour	Action
M22-DLH-W	Extended	White	Momentary
M22-DLH-R		Red	
M22-DLH-G		Green	
M22-DLH-Y		Yellow	
M22-DLH-B		Blue	

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk