



- \* Four frame sizes
- \* Thermal/magnetic - electronic options
- \* Double break contact system (sizes 2 and 3 only)
- \* Also available in 50kA and 100kA
- \* Side panel mounting option
- \* Temperature rating from -25°C up to +70°C
- \* Screw mounting
- \* Worldwide approvals
- \* IEC/EN 6097
- \* Degree of protection IP20

# Moeller

## NZM MCCBs 3 Pole For Motor Protection



### 25kA Frame Size 1 MCCBs - Thermal Magnetic Trip

Part Number	Fault Breaking Capacity (kA)	Setting Range for Overload (A)	Trip Type
NZMB1-M40	25	32 - 40	Thermal/Magnetic
NZMB1-M50		40 - 50	
NZMB1-M63		50 - 63	
NZMB1-M80		63 - 80	
NZMB1-M100		80 - 100	

### 25kA Frame Size 2 MCCBs - Thermal Magnetic Trip

Part Number	Fault Breaking Capacity (kA)	Setting Range for Overload (A)	Trip Type
NZMB2-M125	25	100 - 125	Thermal/Magnetic
NZMB2-M160		125 - 160	
NZMB2-M200		160 - 200	

### 50kA Frame Size 2 MCCBs - Electronic Trip

Part Number	Fault Breaking Capacity (kA)	Setting Range for Overload (A)	Trip Type
NZMN2-ME90	50	45 - 90	Electronic
NZMN2-ME140		70 - 140	
NZMN2-ME220		110 - 220	

### 50kA Frame Size 3 MCCBs - Electronic Trip

Part Number	Fault Breaking Capacity (kA)	Setting Range for Overload (A)	Trip Type
NZMN3-ME220	50	110 - 220	Electronic
NZMN3-ME350		175 - 350	
NZMN3-ME450		225 - 450	

### 50kA Frame Size 4 MCCBs - Electronic Trip

Part Number	Fault Breaking Capacity (kA)	Setting Range for Overload (A)	Trip Type
NZMN4-ME550	50	275 - 550	Electronic
NZMN4-ME875		438 - 875	
NZMN4-ME1400		700 - 1400	

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)