



- \* Four frame sizes
- \* Double break contact system (sizes 2 and 3 only)
- \* Also available in 50kA and 100kA
- \* Side panel mounting option
- \* Temperature rating from -25°C up to +70°C
- \* Screw mounting
- \* Degree of protection IP20

# Moeller

## PN Isolators (NZM style) Manual, Non-Automatic



### Frame Size 1 Isolators - 3 Pole

Part Number	Short time withstand current (t=1 sec) (kA)	Rated Current (A)	Trip Style
PN1-63	2	63	Manual/Non-Automatic
PN1-100		100	
PN1-125		125	

### Frame Size 2 Isolators - 3 Pole

Part Number	Short time withstand current (t=1 sec) (kA)	Rated Current (A)	Trip Style
PN2-160	3.5	160	Manual/Non-Automatic
PN2-200		200	
PN2-250		250	

### Frame Size 3 Isolators - 3 Pole

Part Number	Short time withstand current (t=1 sec) (kA)	Rated Current (A)	Trip Style
PN3-400	12	400	Manual/Non-Automatic
PN3-630		630	

### Frame Size 1 Isolators - 4 Pole

Part Number	Short time withstand current (t=1 sec) (kA)	Rated Current (A)	Trip Style
PN1-4-63	2	63	Manual/Non-Automatic
PN1-4-100		100	
PN1-4-125		125	

### Frame Size 2 Isolators - 4 Pole

Part Number	Short time withstand current (t=1 sec) (kA)	Rated Current (A)	Trip Style
PN2-4-160	3.5	160	Manual/Non-Automatic
PN2-4-200		200	
PN2-4-250		250	

### Frame Size 3 Isolators - 4 Pole

Part Number	Short time withstand current (t=1 sec) (kA)	Rated Current (A)	Trip Style
PN3-4-400	12	400	Manual/Non-Automatic
PN3-4-630		630	

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)