



- \* Single pole changeover 10A rated contacts (100,000 electrical operations min.)
- \* Built in operation indicator (Mechanical flag) & nameplate standard
- \* Optional features lockable test button, diode & LED indication
- \* Test button colour coded blue for DC, red for AC
- \* LED indicator colour coded green for DC, red for AC
- \* Operating temperature from -40°C up to +70°C
- \* DIN Rail / surface mounting, screw terminal or spring clamp relay bases
- \* Approvals include CE, UL, CSA, VDE, LR

## G2R-1 General Purpose Relays



### 5 Pin Flat Plug-in Relays

Part Number	Coil Voltage	No. of Poles	Function	Current Rating (A)	Description
G2R-1-SN/012DC	12 V DC	1P	C/O	10	+ LED Indicator
G2R-1-SN/024AC	24 V AC				
G2R-1-SN/024DC	24 V DC				
G2R-1-SN/048AC	48 V AC				
G2R-1-SN/048DC	48 V DC				
G2R-1-SN/110AC	110 V AC				
G2R-1-SN/110DC	110 V DC				
G2R-1-SN/230AC	230 V AC				+ LED Indicator and Test Button
G2R-1-SNI/024AC	24 V AC				
G2R-1-SNI/024DC	24 V DC				
G2R-1-SNI/110AC	110 V AC				
G2R-1-SNI/230AC	230 V AC				
G2R-1-SND/024DC	24 V DC				+ LED Indicator and Diode Suppressor
G2R-1-SND/048DC	48 V DC				
G2R-1SNDI/024DC	24 V DC				+ Test Button, LED Indicator and Diode Suppressor

### Accessories



P2RF-05-E



P2RF-05-S

### Accessories (Order Separately)

Part Number	Description
P2RF-05-E	5 Pin Relay Base (DIN Rail / surface mounting), screw terminals (Standard)
P2RF-05-S	5 Pin Relay Base (DIN Rail / surface mounting), spring clamp terminals
P2RF-LABEL	Label for P2RF-05-E socket (Pkt-100)

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)