



- * 3 pole changeover with 10A rated contacts (100,000 electrical operations min.)
- * Built in operation indicator (Mechanical flag) & nameplate standard
- * Optional features lockable test button, diode, varistor & LED indication
- * Test button colour coded blue for DC, red for AC
- * LED indicator colour coded green for DC, red for AC
- * Operating temperature from -40°C up to +60°C
- * DIN Rail / surface mounting screw clamp relay bases
- * Approvals include UL, CSA, SEV, DEMKO, NEMKO, TÜV (IEC) and VDE

MKS3 General Purpose Relays



11 Pin Plug-in Relays

Part Number	Coil Voltage	No. of Poles	Function	Current Rating (A)	Description
MKS3PI-5/006AC	6 V AC	3P	C/O	10	+ Test Button and Mechanical Indicator
MKS3PI-5/006DC	6 V DC				
MKS3PI-5/012AC	12 V AC				
MKS3PI-5/012DC	12 V DC				
MKS3PI-5/024AC	24 V AC				
MKS3PI-5/024DC	24 V DC				
MKS3PI-5/048AC	48 V AC				
MKS3PI-5/048DC	48 V DC				
MKS3PI-5/110AC	110 V AC				
MKS3PI-5/110DC	110 V DC				
MKS3PI-5/230AC	230 V AC				
MKS3PIN-5/006AC	6 V AC				+ Test Button, Mechanical and LED Indicators
MKS3PIN-5/006DC	6 V DC				
MKS3PIN-5/012AC	12 V AC				
MKS3PIN-5/012DC	12 V DC				
MKS3PIN-5/024AC	24 V AC				
MKS3PIN-5/024DC	24 V DC				
MKS3PIN-5/048AC	48 V AC				
MKS3PIN-5/048DC	48 V DC				
MKS3PIN-5/110AC	110 V AC				
MKS3PIN-5/110DC	110 V DC				
MKS3PIN-5/230AC	230 V AC				
MKS3PIND5/024DC	24 V DC				+ Test Button + LED, Mechanical Indicator and Diode Suppressor

Accessories



PF113A-E

PF113A-D

PF113A-N

Accessories (Order Separately)

Part Number	Description
PF113A-E	11-Pin Relay Base (DIN Rail mounting)
PF113A-D	11-Pin Relay Base (DIN Rail mounting) Euro style.
PF113A-N	11-Pin Relay Base (DIN Rail mounting) Euro style.
PFC-A1	Relay hold-down clip (Pair) To suit PF083A-E base.

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk