



- * 6A relay output SPDT
- * DIN 48 x 48 standard cut-out
- * Panel mounting option
- * Five selectable time ranges
- * Motor driven timer
- * Operating temperature from -10°C up to +50°C
- * DIN Rail / surface mounting or rear mounting screw terminal bases
- * Approvals include UL / CSA / CE
- * Degree of protection IP40



H2C-8RA Multirange Timers 8 - Pin

Part Number	Voltage	Time Range	Function
H2C-8RA/024AC	24 V AC	1.25 seconds - 30 hours	DOUBLE POLE CHANGE-OVER OFF-delay Timer RETENTIVE - ELECTRICAL RESET
H2C-8RA/110AC	110 V AC		
H2C-8RA/240AC	240 V AC		

H2C-RS Multirange Timers 11 - Pin

Part Number	Voltage	Time Range	Function
H2C-RSA/024AC	24 V AC	1.25 seconds - 30 hours	DOUBLE POLE CHANGE-OVER OFF-delay Timer RETENTIVE - ELECTRICAL RESET
H2C-RSA/110AC	110 V AC		
H2C-RSA/240AC	240 V AC		
H2C-RSB/024AC	24 V AC	0.2 seconds - 6 hours	
H2C-RSB/110AC	110 V AC		
H2C-RSB/240AC	240 V AC		

H2C-S Multirange Timers 11 - Pin

Part Number	Voltage	Time Range	Function
H2C-SA/024AC	24 V AC	1.25 seconds - 30 hours	DOUBLE POLE CHANGE-OVER ON-delay Timer NON-RETENTIVE
H2C-SA/110AC	110 V AC		
H2C-SA/240AC	240 V AC		
H2C-SB/024AC	24 V AC	0.2 seconds - 6 hours	
H2C-SB/110AC	110 V AC		
H2C-SB/240AC	240 V AC		

Accessories



P2CF-08-E



P3G-08



P2CF-11-E



P3GA-11

Accessories (Order Separately)

Part Number	Description
P2CF-08-E	8 - Pin Timer Base (DIN Rail mounting)
P3G-08	8 - Pin Timer Base (panel mounting)
P2CF-11-E	11 - Pin Timer Base (DIN Rail mounting)
P3GA-11	11 - Pin Timer Base (panel mounting)
Y92F-30	Panel mounting clip

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk