



- \* 3A relay output 4PDT
- \* Pin configuration compatible with MY4 relay
- \* Fixed time range
- \* Electronic timer
- \* Operating temperature from -10°C up to +50°C
- \* DIN Rail / surface mounting relay bases
- \* Approvals include UL / CSA / CE
- \* Degree of protection IP40

## H3Y4 Specific Function Timers Plug-in Electronic



H3Y4/S Seconds Timers 14 - Pin			
Part Number	Voltage	Time Range	Function
H3Y4/S1/024AC	24 V AC	0.1 second -	4 Pole Change Over On-Delay Timer
H3Y4/S1/024DC	24 V DC		
H3Y4/S1/110AC	110 V AC		
H3Y4/S1/240AC	240 V AC	1 second	
H3Y4/S5/024AC	24 V AC	0.2 second -	
H3Y4/S5/024DC	24 V DC		
H3Y4/S5/110AC	110 V AC		
H3Y4/S5/240AC	240 V AC	5 seconds	
H3Y4/S10/024AC	24 V AC	0.5 second -	
H3Y4/S10/024DC	24 V DC		
H3Y4/S10/110AC	110 V AC		
H3Y4/S10/240AC	240 V AC	10 seconds	
H3Y4/S30/024AC	24 V AC	1 second -	
H3Y4/S30/024DC	24 V DC		
H3Y4/S30/110AC	110 V AC		
H3Y4/S30/240AC	240 V AC	30 seconds	
H3Y4/S60/024AC	24 V AC	2 seconds -	
H3Y4/S60/024DC	24 V DC		
H3Y4/S60/110AC	110 V AC		
H3Y4/S60/240AC	240 V AC	60 seconds	

### Accessories



PYF14A-E



PYF14A-N

Accessories (Order Separately)	
Part Number	Description
<b>PYF14A-E</b>	14 Pin Relay Base (DIN Rail / surface mounting), screw terminals (Standard)
<b>PYF14A-N</b>	14 Pin Relay Base (DIN Rail / surface mounting), screw terminals (European Style Layout)
<b>Y92H-3</b>	Pair of clips for H3Y4 Timers (PYF14A-E / PYF14A-N) relay bases.
<b>Y92F-78</b>	Panel Adaptor for H3Y4/H3YN (For flush mounting of timer)

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)