



- \* Sheet steel, zinc coated housing
- \* Output voltage compensation
- \* Parallel connection possible
- \* High operational reliability (500,000H MTBF)
- \* 0°C-70°C (>55°C Degrading)
- \* Operating temperature from -25°C up to +70°C
- \* DIN Rail mounting
- \* Approvals include CSA, CE, CURS, UL LISTED
- \* Degree of protection IP20

# Phoenix Contact

## Trio Standard Switched Mode Power Supplies

### Single Phase



### Single Phase Switched Mode Power Supplies

Part Number	Input Voltage	Output Current (A)	Output Voltage	Dimensions (mm) (H x W x D)
2866268	85-264 V AC	2.5	22.5 - 29.5 V DC	130 x 32 x 115
2866310		5		130 x 40 x 115
2866323		10		130 x 60 x 152.5
2866381		20		130 x 115 x 152.5

### Three Phase

- \* Sheet steel, zinc coated housing
- \* Output voltage compensation
- \* Parallel connection possible
- \* High operational reliability (500,000H MTBF)
- \* 0°C-70°C (>55°C Degrading)
- \* Operating temperature from -25°C up to +70°C
- \* DIN Rail mounting
- \* Approvals include CSA, CE, CURS, UL LISTED
- \* Degree of protection IP20



### Three Phase Switched Mode Power Supplies

Part Number	Input Voltage	Output Current (A)	Output Voltage	Dimensions (mm) (H x W x D)
2866462	3 x 320-575 V AC	5	22.5 - 29.5 V DC	130 x 60 x 152.5
2866459		10		130 x 60 x 152.5
2866394		20		130 x 115 x 152.5
2866404		40		130 x 139 x 190

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)