



- \* Break ON & OFF load
- \* Fully visible breaking
- \* Supplied tropicalised
- \* Available to 4000A
- \* Available 9/12 pole to 1600A
- \* For external use requires shaft + handle
- \* DIN Rail / screw mounting
- \* Conforms to IEC 60947-3

# Socomec

## Sirco

### Load Break Switches

### 3 Pole Sirco Switch Bodies Only



#### 3 Pole Sirco Switch Bodies Only

Part Number	Rated Operation Current (A)	kW rating AC23 @ 400V*	Maximum Cable Size (mm <sup>2</sup> )	Minimum Cable Size (mm <sup>2</sup> )
26003004	40	18.5	16	4
26003006	63	25	16	10
26003008	80	40	35	16
26003010	100	40	35	25
26003014	125	63	50	35
26003017	160	80	95	50
26003021	200	100	95	70
26003026	250	132	150	95
26003032	315	160	240	150
26003041	400	220	240	185
26003051	500	280	240	240
26003064	630	280	2 x 300	2 x 150
26003081	800	450	2 x 300	2 x 185
26003100	1000	560	4 x 185	2 x 240
26003120	1250	560	4 x 185	-
26003160	1600	560	6 x 240	-

\* AC23 Rating at 400VAC without prebreak frequent operation

**N.B.** Items to be ordered separately: Handles, Shafts, Auxiliaries, Terminal Screens, Terminal Shrouds - see Accessories/Terminal Covers pages

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)