



- \* Break ON & OFF load
- \* Fully visible breaking
- \* Double break per phase
- \* For external use requires shaft + handle
- \* Rated up to 690 V AC with barriers
- \* Rated insulation voltage 800 V AC
- \* DIN Rail / screw mounting, modular panel with 45mm cutout
- \* Approvals IEC 60947-3, EN 60947-3
- \* Degree of protection IP20

# Socomec

## Sirco M - Accessories



### Handles

M Type External Front Handles					
Part Number	To Switch Size	Handle Size (mm)	Colour	IP Rating	Function
14711111	M1/M2	S00	Black	55	Door Interconnected Front & RHS Handle
14731111				65	
14741111			Red/Yellow	65	
14811111	M3	S0	Black	55	
14831111				65	
14841111			Red/Yellow	65	
14910111	MV	S0	Black	55	External Front & RHS Handle
14930111				65	
14940111			Red/Yellow	65	
14112111		S1	Black	55	External Front Only Handle
14132111				65	
14142111			Red/Yellow	65	

### Shafts

Shafts			
Part Number	To Suit Handle	To Suit Switch	Length (mm)
14070515	S00/S0	M1/M2/M3	150
14070520			200
14070532			320
14090615	S0	MV	150
14090620			200
14090632			320
14010620	S1	MV	200
14010632			320
14010640			400

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)