





- * Valox resin body with acrylic lens
- * Ingress Protection IP67
- * Operating temperature -34°C to +70°C
- * LED status indicators
- * Overload, short circuit & reverse polarity protection
- * Suitable for 1200psi washdown
- * Supplied complete with M30 nut & 2 screws with nuts
- * All other accessories sold separately
- * CE, UL, CSA Approvals






Allen Bradley






Standard Series 9000 Photoelectric Sensors



2m Pre-Cabled Connection

Series 9000 Transmitters		10 - 264V AC / DC			
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	42GRL-9000	Transmitter	61	N/A	N/A
	42GRL-9040	High Power Transmitter	152		

Series 9000 Standard Sensors		10 - 30V DC			NPN/PNP	
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output	
	42GRR-9000	Receiver	Transmitter Dependent	Light On/Dark On Selectable	250mA NPN/PNP Selectable	
	42GRU-9000	Retro Reflective	9			
	42GRU-9200	Polarised Retro Reflective	5			
	42GRP-9000	Diffuse Reflective	1.5			
	42GRP-9040	Long Range Diffuse Reflective	3			

Series 9000 Standard Sensors		70 - 264V AC / DC			Relay	
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output	
	42GRR-9002	Receiver	Transmitter Dependent	Light On/Dark On Selectable	1A SPDT Relay	
	42GRU-9002	Retro Reflective	9			
	42GRU-9202	Polarised Retro Reflective	5			
	42GRP-9002	Diffuse Reflective	1.5			
	42GRP-9042	Long Range Diffuse Reflective	3			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk