







- * Midel body with acrylic lens
- * Ingress Protection IP67
- * Operating temperature -25°C to +55°C
- * LED status indicators
- * Overload, short circuit & reverse polarity protection
- * Suitable for 1200psi washdown
- * Supplied complete with M18 locknut
- * All other accessories sold separately
- * CE, UL, CSA Approvals





Allen Bradley

42EF RightSight Photoelectric Sensors



2m Pre-Cabled Connection

42EF RightSight Photoelectric Sensors				10 - 30V DC		NPN
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output	
	42EF-E1EZB-A2	Transmitter	20	N/A	N/A	
	42EF-R9MNB-A2	Receiver	Transmitter Dependent	Light On/Dark On Selectable	100mA NPN	
	42EF-P2MNB-A2	Polarised Retro Reflective	3			
	42EF-D1MNAK-A2	Diffuse Reflective	0.5			

42EF RightSight Photoelectric Sensors				10 - 30V DC		PNP
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output	
	42EF-E1EZB-A2	Transmitter	20	N/A	N/A	
	42EF-R9MPB-A2	Receiver	Transmitter Dependent	Light On/Dark On Selectable	100mA PNP	
	42EF-P2MPB-A2	Polarised Retro Reflective	3			
	42EF-D1MPAK-A2	Diffuse Reflective	0.5			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk