



- * Oil resistant PVC jacket + PUR connector body
- * 4A nominal current
- * 250V nominal voltage
- * Ingress Protection IP67 in locked position
- * Operating temperature -20°C to +105°C
- * CE, UL, CSA Approvals

Allen Bradley

889D M12 Cordset Leads



Female Single Ended

889D M12 Straight Cordset Leads - Female					
Style	Part Number	No. Wired Pins	Format	Cable Length (m)	Colour
	889D-F4AC-2	4	4 Pole	2	● PVC
	889D-F4AC-5	4	4 Pole	5	
	889D-F4AC-10	4	4 Pole	10	
	889D-F4EC-2	4	4 Pole	2	● PVC + Braided Shield
	889D-F4EC-5	4	4 Pole	5	
	889D-F4EC-10	4	4 Pole	10	
	889D-F5EC-2	5	5 Pole	2	
	889D-F5EC-5	5	5 Pole	5	
	889D-F5EC-10	5	5 Pole	10	
	889D-F6EC-2	6	6 Pole	2	
	889D-F6EC-5	6	6 Pole	5	
	889D-F6EC-10	6	6 Pole	10	

889D M12 Elbow Cordset Leads - Female					
Style	Part Number	No. Wired Pins	Format	Cable Length (m)	Colour
	889D-R4AC-2	4	4 Pole	2	● PVC
	889D-R4AC-5	4	4 Pole	5	
	889D-R4AC-10	4	4 Pole	10	
	889D-R4EC-2	4	4 Pole	2	● PVC + Braided Shield
	889D-R4EC-5	4	4 Pole	5	
	889D-R4EC-10	4	4 Pole	10	
	889D-R5EC-2	5	5 Pole	2	
	889D-R5EC-5	5	5 Pole	5	
	889D-R5EC-10	5	5 Pole	10	
	889D-R6EC-2	6	6 Pole	2	
	889D-R6EC-5	6	6 Pole	5	
	889D-R6EC-10	6	6 Pole	10	

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk