



- \* Heavy duty metal housing
- \* 6A switch rating
- \* Ingress protection IP54 (Nema 13 oiltight)
- \* Operating temperature -18°C to +54°C
- \* CE, UL, CSA Approvals

# Allen Bradley

## 802T 2 Circuit Limit Switches



### M20 Conduit Entry

#### 802T 2 Circuit Limit Switches

Style	Part Number	Description	Operation	Contacts	
				Configuration	Action
	802T-AS6	Rotary Motion	Spring Return	1 N/O + 1 N/C 2 Circuit	Snap Action
	802T-A1S6	Rotary Motion, CW			
	802T-A2S6	Rotary Motion, CCW			
	802T-HS6	Rotary Motion	High Force		
	802T-H1S6	Rotary Motion, CW			
	802T-H2S6	Rotary Motion, CCW			
	802T-ALW5S6	Rotary Motion	Low Force		
	802T-AMS6	Rotary Motion	Maintained		
	802T-NPS6	Rotary Motion	Neutral Position		
	802T-BS6	Top Pin Plunger	Spring Return	1 N/O + 1 N/C 2 Circuit	Snap Action
	802T-CS6	Side Pin Plunger			
	802T-DS6	Top Roller Plunger			
	802T-KS6	Side Roller Plunger			
	802T-K1S6	90° Side Roller Plunger			
	802T-WSS6	Cats Whisker Nylon			
	802T-WS1S6	Cats Whisker Wire			
	802T-CWS6	Coil Spring			

**N.B.** Levers for Rotary Motion switches can be found on page 17

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403 426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)