



- * Stainless steel housing and stainless steel wetted parts
- * Ingress Protection IP65
- * Operating temperature -40°C to +125°C
- * Supply limited to 24V DC above +100°C
- * Loop powered 7 - 35V DC
- * High stability CVD sensing element
- * Cable used must be screened
- * CE, UL, CSA, PEP Approvals

* **Output configured at point of order and not configurable in the field**

Gems

Universal Series 2200 Pressure Transducers



DIN Plug Connector

Series 2200 BGA Pressure Transducers		Loop Powered			
Style	Part Number	Gauge Pressure Range (Bar)	Electrical Connection	Process Connection	Output
	2200BGA1001A3UA	0 - 1.0	DIN Connector (Included)	1/4" BSP G	4 - 20 mA (other configurations available)
	2200BGA1601A3UA	0 - 1.6			
	2200BGA2501A3UA	0 - 2.5			
	2200BGA4001A3UA	0 - 4.0			
	2200BGA6001A3UA	0 - 6.0			

Series 2200 BGB Pressure Transducers		Loop Powered			
Style	Part Number	Gauge Pressure Range (Bar)	Electrical Connection	Process Connection	Output
	2200BGB1001A3UA	0 - 10	DIN Connector (Included)	1/4" BSP G	4 - 20 mA (other configurations available)
	2200BGB1601A3UA	0 - 16			
	2200BGB2501A3UA	0 - 25			
	2200BGB4001A3UA	0 - 40			
	2200BGB6001A3UA	0 - 60			

Series 2200 BGC Pressure Transducers		Loop Powered			
Style	Part Number	Gauge Pressure Range (Bar)	Electrical Connection	Process Connection	Output
	2200BGC1001A3UA	0 - 100	DIN Connector (Included)	1/4" BSP G	4 - 20 mA (other configurations available)
	2200BGC1601A3UA	0 - 160			
	2200BGC2501A3UA	0 - 250			
	2200BGC4001A3UA	0 - 400			

Leeds
Tel: 0113 243 0203

Sheffield
Tel: 0114 243 1841

Gateshead
Tel: 0191 460 2233

Manchester
Tel: 0161 876 4337

Glasgow
Tel: 0141 892 0166

Walsall
Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk