



- \* Plastic nylon construction
- \* Ingress Protection IP65
- \* Operating temperature -20°C to +100°C
- \* Mountable in any orientation
- \* FDA approved materials
- \* CE, UL, CSA Approvals

# Gems

## Turbo-Flow Hall Effect Flow Sensors



### Miniature DIN Plug Connector

FT110 TurboFlow Flow Sensors		5 - 24V DC			
Style	Part Number	Flow Range (L/min)	Electrical Connection	Process Connection	Pulses Per Litre
	FT110/0271006	0.5 - 5	Mini-DIN Connector (Included)	3/8" BSP G	6900
	FT110/0271007	1.0 - 10			3300
	FT110/0271008	1.0 - 15			4600
	FT110/0271009	1.0 - 15			2200
	FT110/0271010	2.0 - 30			1000

FT210 TurboFlow Flow Sensors		5 - 24V DC			
Style	Part Number	Flow Range (L/min)	Electrical Connection	Process Connection	Pulses Per Litre
	FT210/212460E	0.1 - 2.5	Mini-DIN Connector (Included)	1/4" BSP G	22000

# Gems

## FS380P Piston Type Flow Switches

- \* Polypropylene construction
- \* 10VA switch rating
- \* Ingress Protection IP65
- \* Operating temperature -18°C to +100°C
- \* Ideal for coolant applications
- \* CE, UL, CSA Approvals



### 24" Pre-Cabled Connection

FS380P Piston Type Flow Switches					
Style	Part Number	Flow Range (L/min)	Electrical Connection	Process Connection	Output
	FS380P/216445	0.25	24" Pre-Cabled	3/8" NPT Male	SPST N/O at Zero Flow
	FS380P/197081	1.0			
	FS380P/197082	1.9			
	FS380P/197083	3.8			
	FS380P/197084	5.7			
	FS380P/197085	7.6			
	FS380P/216446	0.25	24" Pre-Cabled	1/4" QDC Male	SPST N/O at Zero Flow
	FS380P/197091	1.0			
	FS380P/197092	1.9			
	FS380P/197093	3.8			
	FS380P/197094	5.7			
	FS380P/197095	7.6			

**N.B.** Quick disconnect versions (QDC) require acetal adapters, please see our website for the complete range

**Leeds**  
Tel: 0113 243 0203

**Sheffield**  
Tel: 0114 243 1841

**Gateshead**  
Tel: 0191 460 2233

**Manchester**  
Tel: 0161 876 4337

**Glasgow**  
Tel: 0141 892 0166

**Walsall**  
Tel: 01922 403 426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)