





- \* Plastic construction
- \* 20VA switch rating
- \* Ingress Protection T10: IP65, T5: IP64, T3: IP64
- \* Operating temperature -40°C to +121°C
- \* Compatible for most liquids, oils and chemicals
- \* CE, UL, CSA Approvals

# Gems

## LS7 Single Point Level Switches




### External Mount

LS7 Single Point Level Switches - External Mount					
Style	Part Number	Description	Cable Length (m)	Contacts	
				Configuration	Action
	LS7T10/165800	Polypropylene Float	0.5	SPST	Reed Switch
	LS7T10/165900	Nylon Float			
	LS7T10/182700	Versoplast Float			
	LS7T5/189423	Polypropylene Float	0.5	SPST	Reed Switch
	LS7T5/189422	Versoplast Float			



### Internal Mount

LS7 Single Point Level Switches - Internal Mount					
Style	Part Number	Description	Cable Length (m)	Contacts	
				Configuration	Action
	LS7T3/164520	Polypropylene Float	0.5	SPST	Reed Switch
	LS7T3/182600	Versoplast Float			

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403 426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)