



- * PVC/PP/TPE conductor insulation material
- * Ingress Protection IP67
- * Operating temperature -25°C to +85°C
- * Circular/panel feed through connectors 3 or 4 pole versions available
- * Screened, ethernet & profibus versions also available
- * CE, UL, IEC 60-352-4 & IEC 60-947-5-2 Approvals

Harting

Harax IDC & Valve Connectors



M8 Plug-In Connection

Harax IDC Connectors - M8		Max. 32V DC			
Style	Part Number	Gender	Format	Style	Cable Size
	2102-151-1305	Male	3 Pole	Straight	0.25 - 0.5mm²
	2102-151-2305	Female			
	2102-151-1405	Male	4 Pole		
	2102-151-2405	Female			



M12 Plug-In Connection

Harax IDC Connectors - M12			Max. 32V DC		
Style	Part Number	Gender	Format	Style	Cable Size
	2103-111-1405	Male	4 Pole	Straight	0.25 - 0.5mm ²
	2103-111-2405	Female			
	2101-130-5081	Male	3 Pole	Angled	
	2101-130-5091	Female			
	2101-140-5081	Male	4 Pole	Angled	
	2101-140-5091	Female			



Valve Connectors

Valve Connectors - EN 175301-803			Max. 250V		
Style	Part Number	Style	No. of Poles	Gender	Cable Size
	2109-005-1101	Form A	3 Pole + Earth	Female	0.5 - 1.0mm ²
	2109-005-2201	Form B			0.25 - 0.5mm ²
	2109-005-3101	Form C			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk