



- * Die-cast aluminium alloy construction
- * 5A switch rating
- * Ingress Protection IP65 (IP67 with boot seal)
- * Operating temperature 0°C to +70°C
- * Side and bottom entries available
- * High and low temperature variants available
- * Extra force O-Ring options available
- * CE, UL, CSA Approvals

Honeywell

14CE Sealed Limit Switches



Base Entry - Pre-Cabled Connection

14CE Sealed Limit Switches - Base Entry

Style	Part Number	Description	Cable Length (m)	Contacts	
				Configuration	Action
	14CE1-1	Top Pin Plunger	1	1 N/O + 1 N/C SPDT	Snap Action
	14CE1-3		3		
	14CE1-3K	Top Pin + O-Ring	3		
	14CE18-1	Top Pin + Boot	1		
	14CE18-3		3		
	14CE2-1	Top Roller Plunger	1		
	14CE2-3		3		
	14CE2-3K	Top Roller + O-Ring	3		
	14CE31-1	Top Roller + Boot	1		
	14CE31-3		3		
	14CE3-1	90° Top Roller Plunger	1		
	14CE3-3		3		
	14CE3-3K	90° Top Roller + O-ring	3		
	14CE55-3	90° Top Roller Plunger + Boot	3		
	14CE16-1	Rotary Motion, No Lever	1		
	14CE16-3		3		

Side Entry - Pre-Cabled Connection

14CE Sealed Limit Switches - Side Entry

Style	Part Number	Description	Cable Length (m)	Contacts	
				Configuration	Action
	14CE1-1A	Top Pin Plunger	1	1 N/O + 1 N/C SPDT	Snap Action
	14CE1-3A		3		
	14CE1-3AK	Top Pin + O-Ring	3		
	14CE2-1A	Top Roller Plunger	1		
	14CE2-3A		3		
	14CE2-3AK	Top Roller + O-Ring	3		
	14CE3-1AK	90° Top Roller + O-Ring	1		
	14CE3-3AK		3		

N.B. Levers for Rotary Motion switches can be found on page 38

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk