



- * Die-cast aluminium alloy construction
- * 5A switch rating
- * Ingress Protection IP65 (IP67 with boot seal)
- * Operating temperature 0°C to +70°C
- * Side and bottom entries available
- * High and low temperature variants available
- * Cables required for connection
- * CE, UL, CSA Approvals

Honeywell

14CE Plug-In Sealed Limit Switches



Base Entry - M12 Plug-In Connection

14CE Sealed Limit Switches - Base Entry

Style	Part Number	Description	Entry	Contacts	
				Configuration	Action
	14CE1-Q	Top Pin Plunger	M12 Plug-In	1 N/O + 1 N/C SPDT	Snap Action
	14CE1-KQ	Top Pin Plunger + O-Ring			
	14CE18-Q	Top Pin Plunger + Boot			
	14CE2-Q	Top Roller Plunger			
	14CE2-KQ	Top Roller Plunger + O-Ring			
	14CE3-Q	90° Top Roller Plunger			
	14CE3-KQ	90° Top Roller Plunger + O-Ring			
	14CE16-Q	Rotary Motion, No Lever			

Side Entry - M12 Plug-In Connection

14CE Sealed Limit Switches - Side Entry

Style	Part Number	Description	Entry	Contacts	
				Configuration	Action
	14CE1-AQ	Top Pin Plunger	M12 Plug-In	1 N/O + 1 N/C SPDT	Snap Action
	14CE2-AQ	Top Roller Plunger			

Levers for 14CE16

Style	Part Number	Description	Material	Diameter (mm)	Length (mm)
	LSZ51B	Roller Lever	Metal	19	-
	LSZ51A	Adjustable Roller	Nylon	19	30 - 89
	LSZ54N	Adjustable Rod	Stainless Steel Rod	3.2	Up to 140

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk