








- * Epoxy-sealed rugged die-cast housing
- * 10A switch rating
- * Ingress Protection IP67
- * Operating temperature -25°C to + 85°C
- * CE, UR, CCC Approvals

Honeywell






91MCE Miniature Sealed Limit Switches



Base Entry - Pre-Cabled Connection

91MCE Miniature Sealed Limit Switches - Base Entry					
Style	Part Number	Description	Cable Length (m)	Contacts	
				Configuration	Action
	91MCE1-P1B	Top Pin Plunger	1	1 N/O + 1 N/C SPDT	Snap Action
	91MCE18-P1B	Top Pin Plunger + Boot			
	91MCE2-P1B	Top Roller Plunger			
	91MCE3-P1B	90° Top Roller Plunger			
	91MCE16-P1B	Side Roller Lever			

Side Entry - Pre-Cabled Connection

91MCE Miniature Sealed Limit Switches - Side Entry					
Style	Part Number	Description	Cable Length (m)	Contacts	
				Configuration	Action
	91MCE1-P1	Top Pin Plunger	1	1 N/O + 1 N/C SPDT	Snap Action
	91MCE18-P1	Top Pin Plunger + Boot			
	91MCE2-P1	Top Roller Plunger			
	91MCE3-P1	90° Top Roller Plunger			
	91MCE16-P1	Side Roller Lever			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk