



- * Die-cast aluminium construction
- * 20A switch rating
- * **Ingress Protection IP50 (IP65 with boot seal)**
- * Operating temperature 0°C to +70°C
- * CE, UL, CSA Approvals

Honeywell

BAF3 Enclosed Micro Switches



Right Hand - M20 Conduit Entry

| BAF3 Enclosed Micro Switches - Right Hand Conduit Entry | | | | | |
|---|-----------------|---------------------------|-------|--------------------|-------------|
| Style | Part Number | Description | Entry | Contacts | |
| | | | | Configuration | Action |
| | BAF3-2RN-RHC | Top Pin Plunger + Boot | M20 | 1 N/O + 1 N/C SPDT | Snap Action |
| | BAF3-2RQ9-RHC | Top Roller Plunger | | | |
| | BAF3-2RQN8-RHC | Top Roller Plunger + Boot | | | |
| | BAF3-2RN2-RHC | Top Roller Lever + Boot | | | |
| | BAF3-2RN18-RHC | Coil Spring + Boot | | | |
| | BAF3-2RN18-RHCN | Telescopic Arm + Boot | | | |

Left Hand - M20 Conduit Entry

| BAF3 Enclosed Micro Switches - Left Hand Conduit Entry | | | | | |
|--|-----------------|---------------------------|-------|--------------------|-------------|
| Style | Part Number | Description | Entry | Contacts | |
| | | | | Configuration | Action |
| | BAF3-2RN-LHC | Top Pin Plunger + Boot | M20 | 1 N/O + 1 N/C SPDT | Snap Action |
| | BAF3-2RQ9-LHC | Top Roller Plunger | | | |
| | BAF3-2RQN8-LHC | Top Roller Plunger + Boot | | | |
| | BAF3-2RN2-LHC | Top Roller Lever + Boot | | | |
| | BAF3-2RN18-LHC | Coil Spring + Boot | | | |
| | BAF3-2RN18-LHCN | Telescopic Arm + Boot | | | |

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk