



- * Heavy duty die-cast aluminium housing
- * 10A switch rating
- * Ingress Protection IP50 (IP65 with boot seal)
- * Operating temperature -20°C to +71°C
- * DTE7S have additional mounting holes for retro fit
- * CE, UL, CSA Approvals

Honeywell

DTE7 & DTE7S Enclosed Micro Switches



M20 Conduit Entry

DTE7 Enclosed Micro Switches				2 Hole Mounting	
Style	Part Number	Description	Entry	Contacts	
				Configuration	Action
	DTE7-2RN-C	Top Pin Plunger + Boot	M20	2 N/O + 2 N/C DPDT	Snap Action
	DTE7-2RN2-C	Top Roller Lever			
	DTE7-2RQN8-C	Top Roller Lever + Boot			

DTE7S Enclosed Micro Switches				2 Hole + Additional Screw Mounting	
Style	Part Number	Description	Entry	Contacts	
				Configuration	Action
	DTE7S-2RN-C	Top Pin Plunger + Boot	M20	2 N/O + 2 N/C DPDT	Snap Action
	DTE7S-2RQ9-C	360° Adjustable Top Roller Plunger			
	DTE7S-2RQN8-C	90° Adjustable Top Roller Plunger			
	DTE7S-2RN2-C	Top Roller Lever			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk