



- * Miniature DIN die-cast aluminium body
- * 6A switch rating
- * Ingress Protection IP66
- * Operating temperature -25°C to +85°C
- * Easy retro-fit with mounting centres to EN50041/47
- * CE, UL, CSA, EN60947-5-1 Approvals

Honeywell

GLC(B) Metal Body Limit Switches



PG 13.5 Conduit Entry

GLC(B) Limit Switches					
Style	Part Number	Description	Conduit Entry	Contacts	
				Configuration	Action
	GLCB01B	Top Pin Plunger	PG 13.5	1 N/O + 1 N/C SPDT	Snap Action
	GLCB01C	Top Roller Plunger			
	GLCB01D	Top Roller Lever			
	GLCB01A1A	Side Roller Lever (Plastic Roller)			
	GLCB01A1B	Side Roller Lever (Metal Roller)			
	GLCB01A2A	Adjustable Roller Lever			
	GLCB01E7B	Coil Spring			
	GLCB01A4J	Adjustable Rod			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk