



- * Miniature DIN plastic body
- * 6A switch rating
- * Ingress Protection IP66
- * Operating temperature -25°C to +85°C
- * Easy retro-fit with mounting centres to EN50041/47
- * CE, UL, CSA, EN60947-5-1 Approvals

Honeywell

GLD(B) Double Insulated Limit Switches



PG 13.5 Conduit Entry

GLD(B) Limit Switches					
Style	Part Number	Description	Conduit Entry	Contacts	
				Configuration	Type
	GLDB01B	Top Pin Plunger	PG 13.5	1 N/O + 1 N/C SPDT	Snap Action
	GLDB01C	Top Roller Plunger			
	GLDB01D	Top Roller Lever			
	GLDB01A1A	Side Roller Lever (Plastic Roller)			
	GLDB01A1B	Side Roller Lever (Metal Roller)			
	GLDB01A2A	Adj. Roller Lever (Plastic Roller)			
	GLDB01A2B	Adj. Roller Lever (Metal Roller)			
	GLDB01E7B	Coil Spring			
	GLDB01A4J	Adjustable Rod			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk