



- * Connector housing constructed from self-extinguishing TPU
- * 4A nominal current
- * 60V DC nominal voltage
- * Ingress Protection IP67 in locked position
- * Operating temperature -25°C to +80°C
- * Available in other lengths upon request
- * PUR versions are halogen free
- * CE, UL Approvals

Lumberg

M12 Elbow Cordset Leads



Female Single Ended

M12 Elbow Cordset Leads - Female

Style	Part Number	No. Wired Pins	Format	Cable Length (m)	Colour
	RKWT4-3-06/2M	3	4 Pole	2	 PVC
	RKWT4-3-06/5M	3	4 Pole	5	
	RKWT4-3-06/10M	3	4 Pole	10	
	RKWT4-07/2M	4	4 Pole	2	
	RKWT4-07/5M	4	4 Pole	5	
	RKWT4-07/10M	4	4 Pole	10	
	RKWT5-56/2M	5	5 Pole	2	
	RKWT5-56/5M	5	5 Pole	5	
	RKWT5-56/10M	5	5 Pole	10	

M12 Elbow Cordset Leads - Female

Style	Part Number	No. Wired Pins	Format	Cable Length (m)	Colour
	RKWT4-3-224/2M	3	4 Pole	2	 PUR
	RKWT4-3-224/5M	3	4 Pole	5	
	RKWT4-3-224/10M	3	4 Pole	10	
	RKWT4-225/2M	4	4 Pole	2	
	RKWT4-225/5M	4	4 Pole	5	
	RKWT4-225/10M	4	4 Pole	10	
	RKWT5-228/2M	5	5 Pole	2	
	RKWT5-228/5M	5	5 Pole	5	
	RKWT5-228/10M	5	5 Pole	10	

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk