



- * PBT housing with nickel coated copper locking nut
- * 4A nominal current
- * 30V AC / DC nominal voltage
- * Ingress Protection IP67 in locked position
- * Operating temperature -25°C to +90°C
- * Maximum conductor size 0.75mm²
- * CE, UL Approvals



Lumberg

M12 Wireable Screw Connectors



Female (Packs of 5)



M12 Wireable Screw Connectors (Packs of 5) - Female

Style	Part Number	No. Wired Pins	Format	Style	Cable Gland Diameter (mm)
	RKC4/3/7/PK	3	4 Pole	Straight	0.3 - 6.5
	RKC4/7/PK	4	4 Pole		0.3 - 6.5
	RKC5/7/PK	5	5 Pole		0.3 - 6.5
	RKC8/9/PK	8	8 Pole		0.4 - 8.0
	RKCW4/3/7/PK	3	4 Pole	Elbow	0.3 - 6.5
	RKCW4/7/PK	4	4 Pole		0.3 - 6.5
	RKCW5/7/PK	5	5 Pole		0.3 - 6.5
	RKCW8/9/PK	8	8 Pole		0.4 - 8.0



Male (Packs of 5)

M12 Wireable Screw Connectors (Packs of 5) - Male

Style	Part Number	No. Wired Pins	Format	Style	Cable Gland Diameter (mm)
	RSC3/7/PK	3	4 Pole	Straight	0.3 - 6.5
	RSC4/7/PK	4	4 Pole		0.3 - 6.5
	RSC5/7/PK	5	5 Pole		0.3 - 6.5
	RSC8/9/PK	8	8 Pole		0.4 - 8.0
	RSCW3/7/PK	3	4 Pole	Elbow	0.3 - 6.5
	RSCW4/7/PK	4	4 Pole		0.3 - 6.5
	RSCW5/7/PK	5	5 Pole		0.3 - 6.5
	RSCW8/9/PK	8	8 Pole		0.4 - 8.0

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk