



- * Plastic PBT body with acrylic lens
- * Ingress Protection IP67
- * Operating temperature -25°C to +55°C
- * LED status indicator
- * Short circuit and reverse polarity protection
- * Touch to teach functionality
- * Adjustable model features variable background and foreground suppression
- * Supplied complete with mounting bracket and screws
- * All other accessories sold separately
- * Cables required for plug-in connection
- * CE Approval

Omron

E3G Short Range Photoelectric Sensors



M8 Plug-In Connection

E3G Short Range Photoelectric Sensors		10 - 30V DC			NPN
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3G-L15	Diffuse Reflective (Adjustable Suppression)	0.005 - 0.05	Light On/Dark On Selectable	100mA NPN
	E3G-L35		0.005 - 0.20		

E3G Short Range Photoelectric Sensors		10 - 30V DC			PNP
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3G-L16	Diffuse Reflective (Adjustable Suppression)	0.005 - 0.05	Light On/Dark On Selectable	100mA PNP
	E3G-L36		0.005 - 0.20		



2m Pre-Cabled Connection

E3G Short Range Photoelectric Sensors		10 - 30V DC			NPN
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3G-L11	Diffuse Reflective (Adjustable Suppression)	0.005 - 0.05	Light On/Dark On Selectable	100mA NPN
	E3G-L31		0.005 - 0.20		

E3G Short Range Photoelectric Sensors		10 - 30V DC			PNP
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3G-L12	Diffuse Reflective (Adjustable Suppression)	0.005 - 0.05	Light On/Dark On Selectable	100mA PNP
	E3G-L32		0.005 - 0.20		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk