



- \* Plastic PBT body with acrylic lens
- \* Ingress Protection IP67
- \* Operating temperature -25°C to +55°C
- \* 2 x LED status indicators
- \* Reverse polarity and short circuit protection
- \* High power pin point LED
- \* 3.5mm thick body profile
- \* Accessories sold separately
- \* CE Approval

# Omron

## E3T Flat Pattern Photoelectric Sensors



### 2m Pre-Cabled Connection

E3T Flat Pattern Photoelectric Sensors		12 - 24V DC			NPN
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3T-FT11	Transmitter/Receiver	0.5	Light On	50mA NPN
	E3T-FT12			Dark On	
	E3T-FD11	Diffuse Reflective	0.03	Light On	
	E3T-FD12			Dark On	

E3T Flat Pattern Photoelectric Sensors		12 - 24V DC			PNP
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3T-FT13	Transmitter/Receiver	0.5	Light On	50mA PNP
	E3T-FT14			Dark On	
	E3T-FD13	Diffuse Reflective	0.03	Light On	
	E3T-FD14			Dark On	

**Leeds**

Tel: 0113 243 0203

**Sheffield**

Tel: 0114 243 1841

**Gateshead**

Tel: 0191 460 2233

**Manchester**

Tel: 0161 876 4337

**Glasgow**

Tel: 0141 892 0166

**Walsall**

Tel: 01922 403 426

e-mail: [sales@scatts.co.uk](mailto:sales@scatts.co.uk)

web: [www.scatts.co.uk](http://www.scatts.co.uk)