



- * Plastic PBT body with acrylic lens
- * Ingress Protection IP67
- * Operating temperature -25°C to +55°C
- * 2 x LED status indicators
- * Reverse polarity and short circuit protection
- * High power pin point LED
- * Accessories sold separately
- * CE Approval

Omron

E3T Side Pattern Photoelectric Sensors



2m Pre-Cabled Connection

E3T Side Pattern Photoelectric Sensors 12 - 24V DC					NPN
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3T-ST11	Transmitter/Receiver	1.0	Light On	50mA NPN
	E3T-ST12			Dark On	
	E3T-SR41-C	Polarised Retro Reflective	0.2	Light On	
	E3T-SR42-C			Dark On	
	E3T-SL11	Diffuse Reflective	0.015	Light On	
	E3T-SL12			Dark On	
	E3T-SL21		0.03	Light On	
	E3T-SL22			Dark On	

E3T Side Pattern Photoelectric Sensors 12 - 24V DC					PNP
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	E3T-ST13	Transmitter/Receiver	1.0	Light On	50mA PNP
	E3T-ST14			Dark On	
	E3T-SR43-C	Polarised Retro Reflective	0.2	Light On	
	E3T-SR44-C			Dark On	
	E3T-SL13	Diffuse Reflective	0.015	Light On	
	E3T-SL14			Dark On	
	E3T-SL23		0.03	Light On	
	E3T-SL24			Dark On	

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk