



- * Standard size die-cast zinc alloy housing
- * 10A switch rating
- * Ingress Protection IP67
- * Operating temperature -10°C to +80°C
- * Integral earth terminal
- * CE, UL, CSA Approvals

Omron

WL Metal Body Limit Switches



PG 13.5 Conduit Entry

WL Limit Switches					
Style	Part Number	Description	Conduit Entry	Contacts	
				Configuration	Action
	WLD-G	Top Pin Plunger	PG 13.5	1 N/O + 1 N/C SPDT	Snap Action
	WLS-D-G	Side Pin Plunger			
	WLD2-G	Top Roller Plunger			
	WLS-D2-G	Adjustable Side Roller Plunger			
	WLCA2-G	Side Roller Lever			
	WLCA2-2G	Side Roller Lever with Over Travel			
	WLCA12-G	Adjustable Roller Lever			
	WLCA32-43G	90° Yoke Roller In-Line Rollers			
	WLCA32-41G	90° Yoke Roller Opposable Rollers			
	WLNJ-G	Coil Spring			
	WLCL-G	Adjustable Rod Lever			

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk