



- * Zinc die-cast nickel plated body
- * Ingress Protection IP67
- * Operating temperature -25°C to +55°C
- * 2 x LED status indicators
- * Rotatable plug-in connection for horizontal or vertical mounting
- * Adjustable model features variable background and foreground suppression
- * Visual indication of short circuit
- * Accessories sold separately
- * Cables required for connection
- * CE, UL, CSA Approvals

Pepperl & Fuchs

Visolux MLV12 Photoelectric Sensors



M12 Plug-In Connection

Visolux MLV12 Photoelectric Sensors		10 - 30V DC		NPN/PNP	
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	M+MV12/115971	Transmitter/Receiver	16.0	Light On/Dark On Selectable	200mA NPN/PNP Push/Pull
	MLV12-54/115230	Polarised Retro Reflective	6.5		
	MLV12-54/115794		4.0		
	MLV12-54/128098		15.0		
	MLV12-8H/115786	Diffuse Reflective (Adjustable Suppression)	0.02 - 0.25 Adjustable BGS		

Pepperl & Fuchs

Visolux GLV18 M18 Photoelectric Sensors



M12 Plug-In Connection

- * Polycarbonate Makrolon, glass-fibre-reinforced housing
- * Ingress Protection IP67
- * Operating temperature -25°C to +60°C
- * M18 x 1.0 short body thread form
- * 4 x LED indicators for 360° all round visibility
- * Short circuit and reverse polarity protection
- * Supplied complete with 2 body locknuts and flush mount bracket
- * All other accessories sold separately
- * Cables required for connection
- * CE, UL Approvals

Visolux GLV18 Photoelectric Sensors		10 - 30V DC		PNP	
Style	Part Number	Description	Sensing Range (m)	Switch Mode	Output
	GD+GV18/188547	Transmitter/Receiver	20.0	Light On/Dark On Selectable	100mA PNP
	GLV18-6/188553	Retro Reflective	6.5		
	GLV18-55/188559	Polarised Retro Reflective	4.0		
	GLV18-8/188568	Diffuse Reflective	0.2		
	GLV18-8/188567		0.45		

Leeds

Tel: 0113 243 0203

Sheffield

Tel: 0114 243 1841

Gateshead

Tel: 0191 460 2233

Manchester

Tel: 0161 876 4337

Glasgow

Tel: 0141 892 0166

Walsall

Tel: 01922 403 426

e-mail: sales@scatts.co.uk

web: www.scatts.co.uk